



uniarch

Powered by Uniview Tech.

IP Video Surveillance

RESIDENTIAL | RETAIL | COMMERCIAL | HOSPITALITY



UNIARCH FIXED TURRET NETWORK CAMERAS

Available in 5MP and 8MP input



U-IPC-T115-PF28 (2.8mm Lens) **U-IPC-T115-PF40** (4.0mm Lens)

Uniarch 5MP Fixed Turret Network Camera



KEY FEATURES:

Optics

- Day/Night functionality
- Smart IR, up to 30m (98ft) IR distance
- 3D DNR (Digital Noise Reduction)

Compression

- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)

Network

- ONVIF Conformance

Structure

- Wide temperature range: -30°C ~ 60°C (-22°F ~ 140°F)
- Wide voltage range of ±25%
- Dimensions: Ø118 x 96mm (Ø4.6" x 3.8")
- IK10 vandal resistant
- 3-Axis
- IP67

U-IPC-T118-DPF28 (2.8mm Lens) **U-IPC-T118-DPF40** (4.0mm Lens)

Uniarch 8MP Fixed Turret Network Camera



KEY FEATURES:

Optics

- Day/Night functionality
- Smart IR, up to 30m (98ft) IR distance
- 2D/3D DNR (Digital Noise Reduction)

Compression

- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)
- Triple Streams

Network

- ONVIF Conformance

Structure

- Wide temperature range: -30°C ~ 60°C (-22°F ~ 140°F)
- Humidity: ≤95% RH (non-condensing)
- Power: DC 12V±25%, PoE (IEEE 802.3af)
- Power consumption: Max 5W
- Dimensions (Ø x H): Ø110.5×94.1mm (Ø4.35"×3.7")
- IP67

UNIARCH 8MP H.265 NVR WITH POE SWITCH

Available in 4CH and 8CH input



uniarch
Powered by Uniview Tech.

U-NVR-104LX-P4

Uniarch 4CH 4K/5MP H.265 NVR
with PoE Switch



KEY FEATURES:

- Support Ultra 265, H.265, H.264 video formats
- 4CH Input
- Plug & Play with four independent PoE network interfaces
- Third-party IP cameras supported with ONVIF conformance: Profile S, G and T
- Support 1CH HDMI, 1CH VGA
- HDMI and VGA simultaneous output
- Up to 4K resolution recording
- 1 SATA HDD, up to 10 TB
- Support cloud upgrade

U-NVR-108LX-P8

Uniarch 8CH 4K/8MP H.265 NVR
with PoE Switch



KEY FEATURES:

- Support Ultra 265, H.265, H.264 video formats
- 8CH Input
- Plug & Play with eight independent PoE network interfaces
- Third-party IP cameras supported with ONVIF conformance: Profile S, G and T
- Support 1CH HDMI, 1CH VGA, HDMI at up to 4K(3840 x 2160 pixels) resolution
- HDMI and VGA simultaneous output
- Up to 4K resolution recording
- 1 SATA HDD, up to 10 TB
- Support cloud upgrade

2x TURRET NW CAMERAS + 4CH NVR with PoE Switch + 2TB HDD



uniarch
Powered by Uniview Tech.

U-KIT-4CH2CAM-5MP

Uniarch Surveillance Kit



KIT INCLUDES:

- 2x **U-IPC-T115-PF28** Cameras
- 1x **U-NVR-104LX-P4** NVR with PoE Switch
- 1x **2TB WD** HDD

KEY FEATURES:

- **5MP** Fixed Turret Network Camera
- Day/Night functionality
- 2.8mm Fixed Lens @F2.0
- Smart IR, up to 30m (98ft) IR distance
- 3D DNR (Digital Noise Reduction)
- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)
- ONVIF Conformance
- Wide Temp. Range: -30°C ~ 60°C (-22°F ~ 140°F)
- Wide voltage range of ±25%
- Dimensions: Ø118 x 96mm (Ø4.6" x 3.8")
- IK10 vandal resistant
- 3-Axis
- IP67

U-KIT-4CH2CAM-8MP

Uniarch Surveillance Kit



KIT INCLUDES:

- 2x **U-IPC-T118-DPF28** Cameras
- 1x **U-NVR-104LX-P4** NVR with PoE Switch
- 1x **2TB WD** HDD

KEY FEATURES:

- **8MP** Fixed Turret Network Camera
- Day/Night functionality
- 2.8mm Fixed Lens @F2.0
- Smart IR, up to 30m (98ft) IR distance
- 2D/3D DNR (Digital Noise Reduction)
- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)
- Triple streams
- ONVIF Conformance
- Wide Temp. Range: -30°C ~ 60°C (-22°F ~ 140°F)
- Dimensions: Ø118 x 96mm (Ø4.6" x 3.8")
- Wide voltage range of ±25%
- 3-Axis
- IP67

4x TURRET NW CAMERAS + 4CH NVR with PoE Switch + WD HDD



uniarch
Powered by Uniview Tech.

U-KIT-4CH4CAM-5MP

Uniarch Surveillance Kit



KIT INCLUDES:

- 4x **U-IPC-T115-PF28** Cameras
- 1x **U-NVR-104LX-P4** NVR with PoE Switch
- 1x **2TB WD** HDD

KEY FEATURES:

- **5MP** Fixed Turret Network Camera
- Day/Night functionality
- 2.8mm Fixed Lens @F2.0
- Smart IR, up to 30m (98ft) IR distance
- 3D DNR (Digital Noise Reduction)
- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)
- ONVIF Conformance
- Wide Temp. Range: -30°C ~ 60°C (-22°F ~ 140°F)
- Wide voltage range of ±25%
- Dimensions: Ø118 x 96mm (Ø4.6" x 3.8")
- IK10 vandal resistant
- 3-Axis
- IP67

U-KIT-4CH4CAM-8MP

Uniarch Surveillance Kit



KIT INCLUDES:

- 4x **U-IPC-T118-DPF28** Cameras
- 1x **U-NVR-104LX-P4** NVR with PoE Switch
- 1x **4TB WD** HDD

KEY FEATURES:

- **8MP** Fixed Turret Network Camera
- Day/Night functionality
- 2.8mm Fixed Lens @F2.0
- Smart IR, up to 30m (98ft) IR distance
- 2D/3D DNR (Digital Noise Reduction)
- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)
- Triple streams
- ONVIF Conformance
- Wide Temp. Range: -30°C ~ 60°C (-22°F ~ 140°F)
- Wide voltage range of ±25%
- Dimensions: Ø118 x 96mm (Ø4.6" x 3.8")
- 3-Axis
- IP67

4x TURRET NW CAMERAS + 8CH NVR with PoE Switch + 4TB HDD



uniarch
Powered by Uniview Tech.

U-KIT-8CH4CAM-5MP

Uniarch Surveillance Kit



KIT INCLUDES:

- 4x **U-IPC-T115-PF28** Cameras
- 1x **U-NVR-108LX-P8** NVR with PoE Switch
- 1x **4TB WD** HDD

KEY FEATURES:

- **5MP** Fixed Turret Network Camera
- Day/Night functionality
- 2.8mm Fixed Lens @F2.0
- Smart IR, up to 30m (98ft) IR distance
- 3D DNR (Digital Noise Reduction)
- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)
- ONVIF Conformance
- Wide Temp. Range: -30°C ~ 60°C (-22°F ~ 140°F)
- Wide voltage range of ±25%
- Dimensions: Ø118 x 96mm (Ø4.6" x 3.8")
- IK10 vandal resistant
- 3-Axis
- IP67

U-KIT-8CH4CAM-8MP

Uniarch Surveillance Kit



KIT INCLUDES:

- 4x **U-IPC-T118-DPF28** Cameras
- 1x **U-NVR-108LX-P8** NVR with PoE Switch
- 1x **4TB WD** HDD

KEY FEATURES:

- **8MP** Fixed Turret Network Camera
- Day/Night functionality
- 2.8mm Fixed Lens @F2.0
- Smart IR, up to 30m (98ft) IR distance
- 2D/3D DNR (Digital Noise Reduction)
- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)
- Triple streams
- ONVIF Conformance
- Wide Temp. Range: -30°C ~ 60°C (-22°F ~ 140°F)
- Wide voltage range of ±25%
- Dimensions: Ø118 x 96mm (Ø4.6" x 3.8")
- 3-Axis
- IP67

8x TURRET NW CAMERAS + 8CH NVR with PoE Switch + WD HDD



uniarch
Powered by Uniview Tech.

U-KIT-8CH8CAM-5MP

Uniarch Surveillance Kit



KIT INCLUDES:

- 8x **U-IPC-T115-PF28** Cameras (5MP)
- 1x **U-NVR-108LX-P8** NVR with PoE Switch
- 1x **4TB WD** HDD

KEY FEATURES:

- **5MP** Fixed Turret Network Camera
- Day/Night functionality
- 2.8mm Fixed Lens @F2.0
- Smart IR, up to 30m (98ft) IR distance
- 3D DNR (Digital Noise Reduction)
- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)
- ONVIF Conformance
- Wide Temp. Range: -30°C ~ 60°C (-22°F ~ 140°F)
- Wide voltage range of $\pm 25\%$
- Dimensions: $\varnothing 118 \times 96\text{mm}$ ($\varnothing 4.6" \times 3.8"$)
- IK10 vandal resistant
- 3-Axis
- IP67

U-KIT-8CH8CAM-8MP

Uniarch Surveillance Kit



KIT INCLUDES:

- 8x **U-IPC-T118-DPF28** Cameras (8MP)
- 1x **U-NVR-108LX-P8** NVR with PoE Switch
- 1x **6TB WD** HDD

KEY FEATURES:

- **8MP** Fixed Turret Network Camera
- Day/Night functionality
- 2.8mm Fixed Lens @F2.0
- Smart IR, up to 30m (98ft) IR distance
- 2D/3D DNR (Digital Noise Reduction)
- Ultra 265, H.265, H.264, MJPEG
- ROI (Region of Interest)
- Triple streams
- ONVIF Conformance
- Wide Temp. Range: -30°C ~ 60°C (-22°F ~ 140°F)
- Wide voltage range of $\pm 25\%$
- Dimensions: $\varnothing 118 \times 96\text{mm}$ ($\varnothing 4.6" \times 3.8"$)
- 3-Axis
- IP67



uniarch

Powered by Uniview Tech.

LIFE IN FOCUS

Totally new look ... Totally cost-effective ...

Totally not that complicated!



www.eos.com.au

NSW

02 9749 5888
nsw@eos.com.au

VIC

03 9544 5633
vic@eos.com.au

QLD

07 3252 9272
qld@eos.com.au

WA

08 9249 5911
wa@eos.com.au

© 2021 EOS AUSTRALIA PTY LTD.

All rights reserved. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products.
EOS AUSTRALIA PTY LTD disclaims proprietary interest in the marks and names of others. This document is for informational purposes only.
EOS AUSTRALIA PTY LTD reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind.